



SAMAFE INTERNATIONAL, S.A.

www.samafeintl.com

Manufacturers & Distributors Worldwide

Construction, Erosion Control, Hardware & Chemicals



2) SAFETY FENCE

Used to mark off danger areas at construction sites, road works and excavation sites.

Also used for crowd control and to designate areas and routes at ski resorts, sports field etc.

Temperature range -40°-200°

Materials: HDPE with UV stabilizer

PICTURE	MODEL NO.	MESH OPENING	ROLL SIZE	WEIGHT (grams/m ²)	COLORS
	SR-2	80 x 65mm (3.14" x 2.1/2")	4' x 50' 4' x 100' 4' x 150' etc	120/140/200/ 240/260/280	Orange Green Black Yellow etc
	LB-1	60 x 60mm (2.3/8" x 2.3/8")	4' x 50' 4' x 100' 4' x 150' etc	270/350	Orange Green Black Yellow
	SR-1	65 x 35mm (2.1/2" x 1.3/8")	4' x 50' 4' x 100' 4' x 150' etc	120/140/200/ 240/260/280	Orange Green Black Yellow
	SB-2	66 x 26mm (2.1/2" x 1")	4' x 50' 4' x 100' 4' x 150' etc	160/200/220	Orange Green Black Yellow
	SB-3	100 X 26mm (4" x 1")	4' x 50' 4' x 100' 4' x 150' etc	120	Orange Green Black Yellow
	SB-5	105 x 60mm (4.1/8" x 2.3/8")	4' x 50' 4' x 100' 4' x 150' etc	120	Orange Green Black Yellow